

Versaline 3 way ball valve



Applications: Food and Dairy.

The Versaline 3-way ball valve is suitable for use where there is a requirement for a sanitary full bore valve. Abrasive products (the valve components can withstand the passage of abrasive medium).

Operating Conditions:

1000 WOG. PTFE Seal (230°C max)

Piggable (except the centre branch)

Required air pressure for actuator is 4-7 bar

Ordering Information:

The part numbers for each available size are listed in the chart below. These valves can be supplied with a variety of pipe connection types. The connection components can also be supplied separately for the user to weld on. The common pipe connection types we stock are RJT, IDF, DIN, SMS, SMS Aseptic and clamp.

These valves are Sanitary, not Hygienic or suitable for CIP.

For a fully Hygienic 3-way ball valve please enquire about our EHEDG 3-way shutter valve.

CODE	SIZE	PORT TYPE	TORQUE
VBAPE – 3/07T/89	0.75"	T	15NM
VBAPE – 3/10T/89	1"	T	20NM
VBAPE – 3/15T/89	1.5"	T	30NM
VBAPE – 3/20T/89	2"	T	35NM
VBAPE – 3/25T/89	2.5"	T	45NM
VBAPE – 3/30T/89	3"	T	60NM
VBAPE – 3/40T/89	4"	T	70NM

