

ALL PURPOSE BREWERY (APB) PUMP

Designed to handle any liquid product (Spent grain, trub, yeast, wort, beer & CIP) transfer application in any brewery

CIP scavenge without air-locking

High suction capability

Low shear transfer



Fully hygienic & EHEDG compliant

The key benefits are to provide a high suction capability for handling heavy adjuncts, yeast waste and spent grain. The pump offers particularly low shear transfer of sensitive yeast, has the ability to handle CIP scavenge without air-locking and low NPSH requirements, allowing easy transfer of hot wort without cavitation. It is fully hygienic & EHEDG compliant.

The APB pump is supplied as standard with IP55 & control panel, speed control and a 4-wheeled trolley. Options include integral fully hygienic pressure relief valve, seal flushing pot (for dry running & hot wort transfer), flowmeters, pressure gauges, pump protection strainers & hoses.

ALL PURPOSE BREWERY (APB) PUMP

APB050

PRODUCT	SPENT GRAIN	ADJUNCT	YEAST	BEER	CIP
CAPACITY (M ³ /H)	2.5	3.5	5	10.5	13
PRESSURE (BAR)	6	6	5	2	2
VISCOSITY (cSt)	15000	5000	2500	1.8	1

APB100

PRODUCT	SPENT GRAIN	ADJUNCT	YEAST	BEER	CIP
CAPACITY (M ³ /H)	6	8.5	12	24.5	27
PRESSURE (BAR)	6	6	5	2	2
VISCOSITY (cSt)	15000	5000	2500	1.8	1

APB200

PRODUCT	SPENT GRAIN	ADJUNCT	YEAST	BEER	CIP
CAPACITY (M ³ /H)	11.5	17	23.5	41	46
PRESSURE (BAR)	8	7	5	2	2
VISCOSITY (cSt)	15000	5000	2500	1.8	1

APB300i

PRODUCT	SPENT GRAIN	ADJUNCT	YEAST	BEER	CIP
CAPACITY (M ³ /H)	37	59	78	94	103
PRESSURE (BAR)	12	7	5	2	2
VISCOSITY (cSt)	15000	5000	2500	1.8	1